


U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371		ATTORNEY'S DOCKET NUMBER PG3671USW
INTERNATIONAL APPLICATION NO. PCT/EP00/01446	INTERNATIONAL FILING DATE 23 February 2000	U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 09/936505
TITLE OF INVENTION Metering Valve		
APPLICANT(S) FOR DO/EO/US Anthony Patrick JONES; Gregor John McLennan ANDERSON; Paul Kenneth RAND		
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:		
<ol style="list-style-type: none"> <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. <input checked="" type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (24) indicated below. <input type="checkbox"/> The US has been elected by the expiration of 19 months from the priority date (Article 31). <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371 (c) (2)) <ol style="list-style-type: none"> <input type="checkbox"/> is attached hereto (required only if not communicated by the International Bureau). <input checked="" type="checkbox"/> has been communicated by the International Bureau. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). <input type="checkbox"/> An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)) <ol style="list-style-type: none"> <input type="checkbox"/> is attached hereto. <input type="checkbox"/> has been previously submitted under 35 U.S.C. 154(d)(4). <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3)) <ol style="list-style-type: none"> <input type="checkbox"/> are attached hereto (required only if not communicated by the International Bureau). <input type="checkbox"/> have been communicated by the International Bureau. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. <input checked="" type="checkbox"/> have not been made and will not be made. <input type="checkbox"/> An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)). <input type="checkbox"/> An English language translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)). <input checked="" type="checkbox"/> A copy of the International Preliminary Examination Report (PCT/IPEA/409). <input checked="" type="checkbox"/> A copy of the International Search Report (PCT/ISA/210). 		
Items 13 to 20 below concern document(s) or information included: <ol style="list-style-type: none"> <input checked="" type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. <input checked="" type="checkbox"/> A FIRST preliminary amendment. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment. <input type="checkbox"/> A substitute specification. <input type="checkbox"/> A change of power of attorney and/or address letter. <input type="checkbox"/> A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825. <input type="checkbox"/> A second copy of the published international application under 35 U.S.C. 154(d)(4). <input type="checkbox"/> A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4). <input checked="" type="checkbox"/> Certificate of Mailing by Express Mail <input checked="" type="checkbox"/> Other items or information: 		
Copy of PCT Request Copy of PCT Coversheet		

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 09/936505		INTERNATIONAL APPLICATION NO. PCT/EP00/01446	ATTORNEY'S DOCKET NUMBER PG3671USW																
24. The following fees are submitted:		CALCULATIONS PTO USE ONLY																	
BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :																			
<input type="checkbox"/> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO <input checked="" type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4)		\$1000.00 \$860.00 \$710.00 \$690.00 \$100.00																	
ENTER APPROPRIATE BASIC FEE AMOUNT =		\$860.00																	
Surcharge of \$130.00 for furnishing the oath or declaration later than months from the earliest claimed priority date (37 CFR 1.492 (e)).		<input type="checkbox"/> 20 <input type="checkbox"/> 30	\$0.00																
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>CLAIMS</th> <th>NUMBER FILED</th> <th>NUMBER EXTRA</th> <th>RATE</th> </tr> </thead> <tbody> <tr> <td>Total claims</td> <td>63 - 20 =</td> <td>43</td> <td>x \$18.00</td> </tr> <tr> <td>Independent claims</td> <td>1 - 3 =</td> <td>0</td> <td>x \$80.00</td> </tr> <tr> <td colspan="2">Multiple Dependent Claims (check if applicable)</td> <td><input type="checkbox"/></td> <td>\$0.00</td> </tr> </tbody> </table>		CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	Total claims	63 - 20 =	43	x \$18.00	Independent claims	1 - 3 =	0	x \$80.00	Multiple Dependent Claims (check if applicable)		<input type="checkbox"/>	\$0.00	TOTAL OF ABOVE CALCULATIONS = \$1,634.00	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE																
Total claims	63 - 20 =	43	x \$18.00																
Independent claims	1 - 3 =	0	x \$80.00																
Multiple Dependent Claims (check if applicable)		<input type="checkbox"/>	\$0.00																
<input type="checkbox"/> Applicant claims small entity status. (See 37 CFR 1.27). The fees indicated above are reduced by 1/2.		\$0.00																	
SUBTOTAL =		\$1,634.00																	
Processing fee of \$130.00 for furnishing the English translation later than months from the earliest claimed priority date (37 CFR 1.492 (f)).		<input type="checkbox"/> 20 <input type="checkbox"/> 30 +	\$0.00																
TOTAL NATIONAL FEE =		\$1,634.00																	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable).		<input type="checkbox"/>	\$0.00																
TOTAL FEES ENCLOSED =		\$1,634.00																	
		Amount to be: refunded	\$																
		charged	\$																
a. <input type="checkbox"/> A check in the amount of _____ to cover the above fees is enclosed.																			
b. <input checked="" type="checkbox"/> Please charge my Deposit Account No. <u>07-1392</u> in the amount of <u>\$1,634.00</u> to cover the above fees. A duplicate copy of this sheet is enclosed.																			
c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. <u>07-1392</u> . A duplicate copy of this sheet is enclosed.																			
d. <input type="checkbox"/> Fees are to be charged to a credit card. WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.																			
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.																			
SEND ALL CORRESPONDENCE TO:																			
David J. Levy GlaxoSmithKline Corporate Intellectual Property Five Moore Drive, PO Box 13398 Research Triangle Park, NC 27709 Telephone: 919-483-2370 Fax: 919-483-7988																			
 SIGNATURE Christopher P. Rogers NAME 36,334 REGISTRATION NUMBER September 11, 2001 DATE																			

Rec'd PCT/PTO 16 OCT 2001
09/936505

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: Jones et al.)
Serial No.: NYA) Examiner: NYA
Int'l Appln. No.: PCT/EP00/01446) Art Unit: NYA
Filing Date: 11 Sept 2001) Docket No.: PG3671USW
Title: METERING VALVE)

PRELIMINARY AMENDMENT UNDER 35 USC 111

Commissioner for Patents
Washington D.C. 20231

Sir:

Kindly amend the application as follows. A clean copy of the amended claims is provided herein. Kindly substitute the clean version of the amended claims (as set forth in Appendix A) for the pending claims having the same claim number. A marked-up version of the claim amendments is set forth as follows.

VERSION WITH MARKINGS SHOWING CHANGES MADE TO CLAIMS

1. (Amended) A metering [Metering] valve [for an aerosol container]
comprising:

a valve body defining a metering chamber[; said metering chamber]
having an inlet and an outlet, [said inlet permitting flow of aerosol from said
container to the metering chamber and said outlet permitting dispensing of
aerosol from the metering chamber; the inlet having]

an inlet valve adapted to be reversibly actuatable from an open to a closed
position located at the inlet; and

[the outlet having] an outlet valve adapted to be reversibly actuatable from
a dispensing to a non-dispensing position located at the outlet, wherein said
outlet valve [comprises] includes an outlet valve seat [and] adapted to be in
biasable contact with an outlet valve poppet [in biasable contact therewith].

2. (Amended) [Metering] The metering valve according to claim 1,
wherein said inlet valve [comprises] includes an inlet valve seat [and]
adapted to be in biasable contact with an inlet valve poppet [in biasable
contact therewith].

3. (Amended) [Metering] The metering valve according to [either of
claims 1 or 2] claim 1, wherein the inlet valve [and the outlet valve are
closed] is the closed position and the outlet valve is in the non-dispensing
position when the metering valve is at rest.

4. (Amended) [Metering] The metering valve according to [any of
claims 1 to 3] claim 1, wherein the inlet valve and the outlet valve are
adapted to be independently operable.

5. (Amended) [Metering] The metering valve according to [any of claims 1 to 4] claim 2, wherein [any] the inlet and/or outlet valve poppet [comprises] includes an incompressible material, and wherein [any] the inlet and/or outlet valve seat [comprises] includes a compressible material.

6. (Amended) [Metering] The metering valve according to [any of claims 1 to 4] claim 2, wherein [any] the inlet and/or outlet valve poppet [comprises] includes a compressible material, and [any] wherein the inlet and/or outlet valve seat [comprises] includes an incompressible material.

7. (Amended) [Metering] The metering valve according to [any of claims 2 to 6] claim 2, additionally comprising an inlet valve mover [for moving] adapted to bias the inlet valve poppet [out of contact with the inlet valve seat].

8. (Amended) [Metering] The metering valve according to [any of claims 1 to 7] claim 7, further comprising an outlet valve mover adapted to bias the outlet valve poppet, wherein said outlet valve mover and said inlet valve mover are adapted to be independently operable.

9. (Amended) [Metering] The metering valve according to [either of claims 7 or] claim 8, wherein [either or both of said] the inlet valve mover [or said] and/or the outlet valve mover is adapted to be mechanically actuatable.

10. (Amended) [Metering] The metering valve according to [either of claims 7 or] claim 8, wherein [either or both of] the inlet valve mover [or] and/or the outlet valve mover is adapted to be electrically actuatable.

11. (Amended) [Metering] The metering valve according to claim 10, wherein [either or both of] the inlet valve mover [or] and/or the outlet valve

mover [comprises] include a multi-component strip or wire which is adapted to be deformable in response to electrical current flow.

12. (Amended) [Metering] The metering valve according to claim 11, wherein [said] the multi-component strip or the multi-component wire [comprises] include [multiple] a plurality of layers [of], wherein individual layers of the plurality of layers comprise a metal, and wherein the individual metallic layers are comprised of different metals.

13. (Amended) [Metering] The metering valve according to claim 12, wherein the inlet valve mover and/or the outlet valve mover include the multi-component strip, and wherein the multi-component strip includes [comprises] a bimetallic strip.

14. (Amended) [Metering] The metering valve according to [either of claims 11 or 12] claim 13, wherein the multi component strip [comprises] includes at least one piezoelectric or piezoresistive material.

15. (Amended) [Metering] The metering valve according to claim 11, wherein the inlet valve mover and/or the outlet valve mover include the multi-component wire, and wherein [said] the multi-component wire [comprises] includes a nickel-titanium alloy material.

16. (Amended) [Metering] The metering valve according to [either of claims 7 or] claim 8, wherein [either or both of] the inlet valve mover [or] and/or the outlet valve mover is adapted to be magnetically actuatable.

17. (Amended) [Metering] The metering valve according to claim 16, wherein [either or both of] the inlet valve mover [or] and/or the outlet valve

mover [comprises] includes a magnetic material or [material which is] a magnetically inductive material.

18. (Amended) [Metering] The metering valve according to [either of claims 7 or] claim 8, wherein [either or both of] the inlet valve mover [or] and/or the outlet valve mover is adapted to be pneumatically actuable.

19. (Amended) [Metering] The metering valve according to [either of claims 7 or] claim 8, wherein [either or both of] the inlet valve mover [or] and/or the outlet valve mover is adapted to be hydraulically actuable.

20. (Amended) [Metering] The metering valve according to claim 18, wherein [either or both of] the inlet valve mover [or] and/or the outlet valve mover [comprises] includes a fluid-filled bag or tube adapted to be capable of transferring hydraulic force.

21. (Amended) [Metering] The metering valve according to [any of claims 1 to] claim 20, wherein the outlet valve poppet [has a form selected from the group consisting of] is in the form of a ball, a mushroom, a cone, a disc [and] or a plug.

22. (Amended) [Metering] The metering valve according to [any of claims 2 to 21] claim 20, wherein the inlet valve poppet [has a form selected from the group consisting of] is in the form of a ball, a mushroom, a cone, a disc [and] or a plug.

23. (Amended) [Metering] The metering valve according to [any of claims 1 to 22] claim 1, wherein said valve body additionally defines a sampling chamber, and wherein the inlet [permits] is adapted to permit flow from the sampling chamber to the metering chamber.

24. (Amended) [Metering] The metering chamber according to [any of claims 1 to] claim 23, wherein the metering chamber [has] is adapted to have a fixed volume.

25. (Amended) [Metering] The metering valve according to [any of claims 1 to] claim 23, wherein the metering chamber [has] is adapted to have a variable metering volume.

Kindly cancel claims 26-63 without prejudice to the filing of claims, prospectively, directed to the subject matter therein.

CLEAN VERSION OF THE AMENDED CLAIMS

1. (Amended) A metering valve comprising:
a valve body defining a metering chamber having an inlet and an outlet,
an inlet valve adapted to be reversibly actuatable from an open to a closed
position located at the inlet; and
an outlet valve adapted to be reversibly actuatable from a dispensing to a
non-dispensing position located at the outlet, wherein said outlet valve
includes an outlet valve seat adapted to be in biasable contact with an outlet
valve poppet.
2. (Amended) The metering valve according to claim 1, wherein said
inlet valve includes an inlet valve seat adapted to be in biasable contact with
an inlet valve poppet.
3. (Amended) The metering valve according to claim 1, wherein the
inlet valve is in the closed position and the outlet valve is in the non-dispensing
position when the metering valve is at rest.
4. (Amended) The metering valve according to claim 1, wherein the
inlet valve and the outlet valve are adapted to be independently operable.
5. (Amended) The metering valve according to claim 2, wherein the
inlet and/or outlet valve poppet includes an incompressible material, and
wherein the inlet and/or outlet valve seat includes a compressible material.
6. (Amended) The metering valve according to claim 2, wherein the
inlet and/or outlet valve poppet includes a compressible material, and
wherein the inlet and/or outlet valve seat includes an incompressible
material.

7. (Amended) The metering valve according to claim 2, additionally comprising an inlet valve mover adapted to bias the inlet valve poppet.

8. (Amended) The metering valve according to claim 7, further comprising an outlet valve mover adapted to bias the outlet valve poppet, wherein said outlet valve mover and said inlet valve mover are adapted to be independently operable.

9. (Amended) The metering valve according to claim 8, wherein the inlet valve mover and/or the outlet valve mover is adapted to be mechanically actuatable.

10. (Amended) The metering valve according to claim 8, wherein the inlet valve mover and/or the outlet valve mover is adapted to be electrically actuatable.

11. (Amended) The metering valve according to claim 10, wherein the inlet valve mover and/or the outlet valve mover include a multi-component strip or wire which is adapted to be deformable in response to electrical current flow.

12. (Amended) The metering valve according to claim 11, wherein the multi-component strip or the multi-component wire include a plurality of layers, wherein individual layers of the plurality of layers comprise a metal, and wherein the individual metallic layers are comprised of different metals.

13. (Amended) The metering valve according to claim 12, wherein the inlet valve mover and/or the outlet valve mover include the multi-

component strip, and wherein the multi-component strip includes a bimetallic strip.

14. (Amended) The metering valve according to claim 13, wherein the multi component strip includes at least one piezoelectric or piezoresistive material.

15. (Amended) The metering valve according to claim 11, wherein the inlet valve mover and/or the outlet valve mover include the multi-component wire, and wherein the multi-component wire includes a nickel-titanium alloy material.

16. (Amended) The metering valve according to claim 8, wherein the inlet valve mover and/or the outlet valve mover is adapted to be magnetically actuatable.

17. (Amended) The metering valve according to claim 16, wherein the inlet valve mover and/or the outlet valve mover includes a magnetic material or a magnetically inductive material.

18. (Amended) The metering valve according to claim 8, wherein the inlet valve mover and/or the outlet valve mover is adapted to be pneumatically actuatable.

19. (Amended) The metering valve according to claim 8, wherein the inlet valve mover and/or the outlet valve mover is adapted to be hydraulically actuatable.

20. (Amended) The metering valve according to claim 18, wherein the inlet valve mover and/or the outlet valve mover includes a fluid-filled bag or tube adapted to be capable of transferring hydraulic force.

21. (Amended) The metering valve according to claim 20, wherein the outlet valve poppet is in the form of a ball, a mushroom, a cone, a disc or a plug.

22. (Amended) The metering valve according to claim 20, wherein the inlet valve poppet is in the form of a ball, a mushroom, a cone, a disc or a plug.

23. (Amended) The metering valve according to claim 1, wherein said valve body additionally defines a sampling chamber, and wherein the inlet is adapted to permit flow from the sampling chamber to the metering chamber.

24. (Amended) The metering chamber according to claim 23, wherein the metering chamber is adapted to have a fixed volume.

25. (Amended) The metering valve according to claim 23, wherein the metering chamber is adapted to have a variable metering volume.

REMARKS

The Examiner is invited to contact the undersigned should there be any questions or concerns.

Respectfully submitted,

Date: 16 Oct 2001


Christopher P. Rogers
Reg. No. 36,334
Attorney for Applicants

GlaxoSmithKline Corporation
Corporate Intellectual Property
Five Moore Drive
PO Box 13398
Research Triangle Park, NC 27709-3398
Direct Phone (919)483-1240
Facsimile (919)483-7977

Metering valve

This invention relates to a metering valve for an aerosol container. The valve is particularly suitable for use in the metered dispensing of medicament by way of
5 an inhalation device.

It is known to dispense medicament in aerosol form from a metered dose inhalation device. Such devices commonly comprise a housing and supported therein, a container for the aerosol formulation. The container has a metering
10 valve which generally is a slide or rotary valve. The slide or rotary valve comprises a valve stem which is movable against a restraining, generally frictional, force within a valve body from a dispensing position to a non-dispensing position.

15 In more detail, a slide valve typically comprises a valve body and within the valve body a sealing ring. A valve stem having a dispensing passage therein is frictionally received by the sealing ring. The valve stem is slidably movable within the sealing ring from a valve-closed position to a valve-open position in which the interior of the valve body is in communication with the dispensing
20 passage. An illustrative slide valve is described in PCT application no. WO96/28367.

Actuation of a slide valve involves the application of sufficient mechanical force to overcome the frictional force between the valve stem and the sealing ring.
25 In currently marketed inhalation devices the mechanical force required to actuate the slide valve is generally of the order of 20-40N. This force is often supplied by the patient manually depressing the container and valve body attached thereto relative to the housing and valve stem supported thereby. The movement of the valve body relative to the valve stem results in actuation of the
30 valve and hence release of medicament.

With some current inhalation devices having a slide or rotary valve the valve stem sometimes tends to stick, pause, or drag during the actuation cycle with the result that the patient can in some circumstances perceive a resistance as
35 the valve stem is moved. This may be partly caused by medicament sedimenting

or precipitating out of the aerosol formulation and depositing on the internal valve components, the presence of medicament on the sliding interface increasing the frictional force between the valve stem and the frictional seal. Various solutions to the problem of valve resistance have been suggested
5 including the use of lubricant on the valve stem and the seal.

It may be understood that effective delivery of medicament to the patient using an inhalation device as described above is to an extent dependent on the patient's ability to co-ordinate the actuation of the device (e.g. firing of the aerosol) with the taking of a sufficiently strong inward breath. The required co-ordination can present difficulties to some patients, with the risk that these patients do not receive the appropriate dose of medicament. There have thus, been efforts to develop inhalation devices which do not rely on manual actuation by the patient, in particular those which are actuatable in response to the breath of
10 a patient. These devices are often known as breath-actuable devices.
15

Breath-actuable devices typically comprise a source of stored energy which on release actuates the slide valve of the medicament container and hence releases medicament, and a breath trigger which triggers the release of the
20 stored energy in response to the breath of the patient. The stored energy source is required because the force required to actuate the slide valve (e.g. 20-40N as mentioned above) is too great to be suppliable by the patient's breath alone. Illustrative breath-actuable devices are described in U.S. patent no. 5,655,523.

25 The applicants have now developed a metering valve which may be actuated without any need for a dispensing stem or other dispensing member to be moved relative to a valve body. Since the new valve requires no relative movement of a valve stem to the valve body the problem of resistance associated with some slide and rotary valves is eliminated.

30 The newly developed metering valve is furthermore, operable by the application of a significantly lower force than is required to operate a conventional metering valve having a slide or rotary valve. The force required can indeed, be so low that the valve is actuatable by the force of a patient's breath alone. The present
35 metering valve is thus, particularly suitable for use in breath-activated devices.

Such devices can be much simpler than current breath-actuated devices because they do not necessarily require a source of stored energy.

EP-A-567,348 describes a metering valve for an aerosol container having a two-stage compress and release mechanism to fill the valve and dispense therefrom. The valve includes metering and dispensing members connected by a central bellows assembly or flexible membrane for relative linear movement into and out of positive sealing engagement with oppositely facing valve seats provided on a fixed valve housing and the metering member respectively. The metering valve herein requires no such central bellows feature.

According to the present invention there is provided a metering valve for an aerosol container comprising a valve body defining a metering chamber; said metering chamber having an inlet and an outlet, said inlet permitting flow of aerosol from said container to the metering chamber and said outlet permitting dispensing of aerosol from the metering chamber; the inlet having an inlet valve reversibly actuatable from an open to a closed position; and the outlet having an outlet valve reversibly actuatable from a dispensing to a non-dispensing position, wherein said outlet valve comprises a outlet valve seat and an outlet valve poppet in biasable contact therewith.

As used herein the term valve poppet means any element which is receivable by a valve seat to form a valve seal and which is movable from the valve seat to break the valve seal. The valve poppet can be of essentially any suitable shape. The biasable contact between the outlet valve seat and outlet valve poppet may be provided by any suitable biasing means, such as a spring.

The metering valve herein enables dispensing of aerosol contents without the need for movement of a dispensing member relative to the valve body. In particular, the metering valve herein does not require the sliding or rotary movement of a valve stem relative to the valve body.

The metering valve herein is preferably designed to provide a non-convoluted flow passageway from the inlet to the outlet of the metering chamber.

Preferably, the metering valve forms a single integral unit which may conveniently be fitted onto known aerosol containers for use in the dispensing of medicament.

5 Preferably, the inlet valve comprises an inlet valve seat and an inlet valve poppet in biasable contact therewith. The biasable contact may be provided by any suitable biasing means (e.g. a spring).

10 Preferably, either one of the inlet and outlet valves is closed when the metering valve is in a rest position. More preferably both the inlet and outlet valves are closed when the metering valve is at rest.

15 Preferably, the inlet and outlet valves are operable independently. Their operation may however, be coupled by using of a suitably coupled trigger system.

20 In one aspect, any valve poppet comprises a hard, incompressible material and any valve seat comprises a softer, compressible material. In another aspect, any valve poppet comprises a soft, compressible material and any valve seat comprises a harder, incompressible material.

25 Alternatively, the inlet and outlet valve poppets and respective valve seats may both comprise hard, incompressible materials having smooth surfaces to ensure good sealing.

30 Preferably, the valve additionally comprises an outlet valve mover for moving the outlet valve poppet out of contact with the outlet valve seat.

35 Preferably, the valve additionally comprises an inlet valve mover for moving the inlet valve poppet out of contact with the inlet valve seat.

In one aspect, either or both of said inlet valve mover or said outlet valve mover is mechanically actuatable. That is to say, actuatable by application of mechanical force either directly or through a mechanism capable of transferring mechanical force.

In another aspect, either or both of the inlet valve mover or the outlet valve mover is electrically actuatable. That is to say actuatable by application of electrical current. More preferably, either or both of the inlet valve mover or the outlet valve mover comprises a multi-component strip or wire which is deformable in response to electrical current flow.

Suitable multi-component strips typically comprise a plurality of layers of material, each material having a different coefficient of thermal expansion. Preferred examples of multi-component strips include strips comprising multiple layers of different metals (e.g. bimetallic strips) and strips comprising at least one piezoelectric or piezoresistive material. Suitable piezoelectric materials include piezoelectric ceramics, such as compounds of lead zirconate and lead titanate, and piezoelectric crystals which are generally polycrystalline ferroelectric materials with the perovskite structure.

Suitable multi-component wires comprise an alloy which undergoes a phase transition on heating which results in contraction thereof. Typically the degree of contraction is from 2% to 8%. Such alloys are generally known as shape memory alloys. Certain shape memory alloys also undergo a change in shape on recooling. Such two way shape memory alloys are also envisaged for use herein.

In one embodiment, the alloy is preferably a nickel-titanium alloy such as a nickel-titanium alloy comprising from 5% to 95%, preferably from 20% to 80%, nickel by weight and from 95% to 5%, preferably from 80% to 20%, titanium by weight. By nickel-titanium alloy it is meant an alloy comprised essentially of nickel and titanium, although other elements may be present in small (e.g. trace) amounts.

In other embodiments, the alloy is preferably a copper-aluminium-nickel alloy or a copper-zinc-aluminium alloy. Trace amounts of other elements may also be present.

Suitable wires typically have a diameter from 30 to 400 micrometers, preferably from 50 to 150 micrometers.

Preferably, either or both of the inlet valve mover or the outlet valve mover is magnetically actuatable.

5 Preferably, either or both of the inlet valve mover or the outlet valve mover comprises magnetic material or material which is magnetically inductive, that is to say material into which magnetism can be induced. The material may be permanently or non-permanently magnetisable.

10 Preferably, either or both of the inlet valve mover or the outlet valve mover is pneumatically actuatable.

15 Preferably, either or both of the inlet valve mover or the outlet valve mover is hydraulically actuatable. More preferably, either or both of the inlet valve mover or the outlet valve mover comprises means, such as a fluid-filled bag or tube capable of transferring hydraulic force.

20 Preferably, the outlet valve poppet and/or the inlet valve poppet comprises an element in the form of a ball, a mushroom, a cone, a disc or a plug.

25 Preferably, the valve body additionally defines a sampling chamber and the inlet permits flow from the sampling chamber to the metering chamber.

The metering chamber is preferably shaped to minimise the surface contact area with the aerosol and thereby reduce deposition of medicament thereon.

In one aspect, the metering chamber has a fixed volume.

30 In another aspect, the metering chamber is of variable volume. The volume of the metering chamber may for example be varied to provide the optimum amount of medicament for release. In one preferred aspect, the volume of the metering chamber is variable automatically in response to a dosing signal sent from an electronic information processor.

- Various types of variable volume metering chambers are envisaged. Suitable chambers comprise a fixed volume chamber whose metering volume is variable by insertion of a plunger or piston. The piston or plunger may have fixed form or alternatively may comprises an element of variable shape and volume such as an inflatable balloon. Other suitable chambers comprise a chamber which is expandable because it is formed from a flexible/expandable material. Further suitable chambers have telescopic or concertina arrangements to allow for mechanical expansion of the metering volume.
- 5 According to another aspect of the present invention there is provided an aerosol container comprising a metering valve as described above.
- In a preferred aspect the valve body of the metering valve is not movable relative to the container. Also, the metering valve contains no movable stem. This
- 10 contrasts with current slide valves where actuation of the valve is achievable by relative movement of the aerosol container to the valve stem.
- In one aspect, the aerosol container comprises a suspension of a medicament in a propellant. More preferably, the propellant is liquefied HFA134a, HFA-227 or
- 15 carbon dioxide. More preferably, the medicament is selected from the group consisting of albuterol, salmeterol, fluticasone propionate, beclomethasone dipropionate, salts or solvates thereof and any mixtures thereof.
- 20 In another aspect, the aerosol container comprises a compressed gas, preferably compressed air.
- According to a further aspect of the present invention there is provided an inhalation device for dispensing medicament to a patient comprising a housing; an aerosol container, locatable within said housing, said aerosol container
- 25 comprising a metering valve as described above; and an outlet valve trigger for triggering the movement of the outlet valve poppet out of contact with the outlet valve seat.

When the aerosol container comprises an inlet poppet valve the inhalation device preferably also comprises an inlet valve trigger for triggering the movement of the inlet valve poppet out of contact with the inlet valve seat.

- 5 Preferably, either or both of said outlet valve trigger or said inlet valve trigger is triggerable in response to the breath of a patient. The outlet valve or inlet valve triggers may be triggerable in response to the inward breath of the patient, or alternatively triggerable at a trigger point which is coupled to the end of the exhalation part of the patient's breath cycle. Inhalation devices which are
10 triggerable at the end of the exhalation part of the breath cycle are described in UK patent application no. 9905134.4 (attorney's docket CGP/PG3614).

Preferably, either or both of the outlet valve trigger or the inlet valve trigger communicates with a sensor which senses the breath of a patient.

- 15 In one aspect, the sensor comprises a breath-movable element which is movable in response to the breath of a patient. Preferably, the breath-movable element is selected from the group consisting of a vane, a sail, a piston and an impeller.
20 In another aspect, the sensor comprises a pressure sensor for sensing the pressure profile associated with the breath of a patient.
25 In a further aspect, the sensor comprises an airflow sensor for sensing the airflow profile associated with the breath of a patient.

In a further aspect, the sensor comprises a temperature sensor for sensing the temperature profile associated with the breath of a patient.

- 30 In a further aspect, the sensor comprises a moisture sensor for sensing the moisture profile associated with the breath of a patient.
In a further aspect, the sensor comprises a gas sensor for sensing the oxygen or carbon dioxide profile associated with the breath of a patient.

In a further aspect, the sensor comprises a piezoelectric or piezoresistive element.

- 5 The outlet valve trigger and the inlet valve trigger may be independently triggerable or they may be triggerable in a coupled fashion.

10 Preferably, either or both of the outlet valve trigger or the inlet valve trigger is a mechanical trigger. In one aspect, the mechanical trigger comprises a lever mechanism. In another aspect, the mechanical trigger comprises a torque transfer mechanism.

15 Preferably, either or both of the outlet valve trigger or the inlet valve trigger comprises a multi-component strip which is deformable in response to electrical current flow. The multi-component strip typically comprises a plurality of layers of material, each material having a different coefficient of thermal expansion. Preferred examples of multi-component strips include strips comprising multiple layers of different metals (e.g. bimetallic strips) and strips comprising at least one piezoelectric or piezoresistive material.

20 Preferably, either or both of the outlet valve trigger or the inlet valve trigger is a magnetic trigger.

25 In one aspect, the outlet valve trigger interacts magnetically with the outlet valve poppet and/or the inlet valve trigger interacts magnetically with the inlet valve poppet.

30 In another aspect, the outlet valve trigger interacts magnetically with a outlet shuttle contacting the outlet valve poppet and/ or the inlet valve trigger interacts magnetically with an inlet shuttle contacting the inlet valve poppet. Preferably, the outlet shuttle and/or inlet shuttle comprises magnetic material.

In a further aspect, the outlet shuttle comprises material which is magnetically inductive and the outlet valve trigger comprises an inductive element capable of inducing magnetism therein and/or the inlet shuttle comprises material which is

magnetically inductive and the inlet valve trigger comprises an inductive element capable of inducing magnetism therein.

5 Preferably, either or both of the outlet valve trigger or the inlet valve trigger is a pneumatic trigger.

10 Preferably, either or both of the outlet valve trigger or the inlet valve trigger is a hydraulic trigger. More preferably, the hydraulic trigger comprises a fluid-filled bag or tube capable of transferring hydraulic force.

15 The invention will now be described further with reference to the accompanying drawing in which:

20 Figure 1 is a sectional view of a first metering valve in accord with the present invention;

25 Figure 2 is a sectional view of a second metering valve in accord with the present invention;

30 Figure 3 is a sectional view of a third metering valve in accord with the present invention;

35 Figure 4 is a sectional view of a fourth metering valve in accord with the present invention;

Figure 5a is a sectional view of a fifth metering valve in accord with the present invention;

Figure 5b is a sectional view of a detail of the valve of Figure 5a;

Figure 6 is a sectional view of a sixth metering valve in accord with the present invention;

Figure 7 is a plan view of the valve actuation mechanism of a seventh metering valve in accord with the present invention;

Figures 8a to 8d show various forms of poppet valve suitable for use in accord with the invention;

5 Figure 9 is a sectional view of an eighth metering valve in accord with the invention.

Figure 10 is a sectional view of a ninth metering valve in accord with the invention;

10 Figure 11 is a sectional view of a tenth metering valve in accord with the invention;

15 Figure 12 is a sectional view of an eleventh metering valve in accord with the invention;

Figure 13 is a sectional view of a twelfth metering valve in accord with the invention;

20 Figure 14 is a sectional view of a thirteenth metering valve in accord with the invention; and

Figure 15 is a schematic view of an inhalation device in accord with the present invention.

25 Figure 1 shows an aerosol metering valve herein. The valve comprises a valve body 10 which defines a metering chamber 12 and a sampling chamber 14. The metering chamber 12 has an inlet 20 permitting flow of aerosol from the sampling chamber 14 which in turn receives aerosol from a container (not shown) and an outlet 30 permitting dispensing of aerosol from the metering chamber 12. The inlet 20 is provided with valve means comprising a valve seat 22 and a valve poppet in the form of a metal ball 24. The metal ball 24 is biased towards the valve seat 22 by the action of spring 26. The outlet 30 is also provided with valve means comprising a valve poppet in the form of a metal ball 34 held by a spring 36 in biased contact with a valve seat 32. The valve body 10

is within a housing 6 shaped such as to define a circular track 8 running upwardly in parallel with the exterior of the valve body 10. Within the track 8 is contained a magnetic ring 40 which is movable up and down the track 8.

- 5 Actuation of the valve of Figure 1 is achievable by movement of the magnetic ring 40 which can magnetically interact with the metal ball poppets 24,34 to dislodge them from their seats 22, 32. Movement of magnetic ring itself is for example, achievable by use of a second magnet (not shown). In a typical operation the inlet 20 valve will first be opened to allow metered flow of aerosol
10 from the sampling chamber 14 into the metering chamber 12. The outlet 30 valve is then opened to allow for dispensing of the aerosol.

Figure 2 shows an aerosol metering valve herein. The valve comprises a valve body 110 which defines a metering chamber 112 and a sampling chamber 114.
15 The metering chamber has an inlet 120 permitting flow of aerosol from the sampling chamber 114 and an outlet 130 permitting dispensing of aerosol from the metering chamber 112. The inlet 120 is provided with valve means comprising a valve seat 122 and a valve poppet in the form of a resilient ball 124. The ball 124 is biased towards the valve seat 122 by the action of spring
20 126. The outlet 130 is also provided with valve means comprising a valve poppet in the form of a ball 134 biased into contact with a valve seat 132 by action of spring 136. The valve body 110 is within housing 106 and the housing is provided with fixing screws 105, 107 for fixing the valve to an aerosol container (not shown). Movable magnetic rings 140, 142 contact the resilient balls 124,
25 134 of the inlet 120 and outlet 130 valves respectively. The magnetic rings 140, 142 are in turn in magnetic communication with shuttle magnets 150 and 152.

Actuation of the metering valve of Figure 2 is achievable by movement of the magnetic rings 140, 142 to physically dislodge the resilient balls 124, 134 from their respective seats 122, 132. Movement of magnetic rings is achievable by movement of the shuttle magnets 150, 152. The shuttle magnets 150, 152 may, in turn be coupled to a mechanical trigger such as a lever mechanism (not shown). In a typical operation the inlet 120 valve will first be opened to allow metered flow of aerosol from the sampling chamber 114 into the metering

chamber 112. The outlet 130 valve is then opened to allow for dispensing of the aerosol.

Figure 3 shows an aerosol metering valve herein. The valve comprises a valve body 210 which defines a metering chamber 212. The metering chamber has an inlet 220 permitting flow of aerosol from a container (not shown) and an outlet 230 permitting dispensing of aerosol from the metering chamber 212. The inlet 220 is provided with valve means comprising a valve seat 222 and a valve poppet in the form of a resilient plastic ball 224. The ball 224 is biased towards the valve seat 222 by the action of spring 226. The outlet 230 is also provided with valve means comprising a valve poppet in the form of a resilient plastic ball 234 biased into contact with a valve seat 232 by action of spring 236. The valve body 210 is within a housing 206. The housing 206 shaped is such as to define two circular cavities 208, 209, each running upwardly in parallel with a portion of the exterior of the valve body 210 and respectively positioned around the inlet 220 and outlet 230 valves. First and second circular solenoid cores 240, 242 are movably located within the first and second circular cavities 208, 209 and respectively engage the inlet and outlet ball valves 224, 234. The circular solenoid cores 240, 242 are in turn, positioned for inductive communication with outer solenoid coil windings magnets 250 and 252. The solenoid coil windings 250, 252 are connected to an electrical power source (not shown).

Actuation of the metering valve of Figure 3 is achievable by movement of the circular solenoid cores 240, 242 to physically dislodge the resilient balls 224, 234 in an upward direction from their respective seats 222, 232. Movement of the circular solenoid cores 240, 242 is in turn achievable by the application of electrical current to the solenoid coil windings 250, 252. In a typical operation the inlet 220 valve will first be opened to allow metered flow of aerosol into the metering chamber 212. The outlet 230 valve is then opened to allow for dispensing of the aerosol.

Figure 4 shows an aerosol metering valve herein. The valve comprises a valve body 310 which defines a metering chamber 312 and a sampling chamber 314. The metering chamber 312 has an inlet 320 permitting flow of aerosol from the sampling chamber 314 and an outlet 330 permitting dispensing of aerosol from

the metering chamber 312. The inlet 320 is provided with valve means comprising a valve seat 322 and a valve poppet in the form of a resilient ball 324. The ball 324 is biased towards the valve seat 322 by the action of spring 326. The outlet 330 is also provided with valve means comprising a valve poppet 5 in the form of a resilient ball 334 biased into contact with a valve seat 332 by action of spring 336. Gripping arms 340, 342 grip the resilient balls 324, 334 of the inlet 320 and outlet 330 valves respectively. The gripping arms are formed from a bimetallic strip wherein each of the bimetallic components thereof has a different coefficient of thermal expansion. The gripping arms 340, 342 are 10 connectable to an electrical power source (not shown).

Actuation of the metering valve of Figure 4 is achievable by movement of the gripping arms 340, 342 to physically dislodge the resilient balls 324, 334 from their respective seats 322, 332. Movement of the gripping arms 340, 342 is in 15 turn achievable by the application of electrical current which causes deformation of the bimetallic strip from which the arms 340, 342 are formed. In a typical operation the inlet 320 valve will first be opened to allow metered flow of aerosol into the metering chamber 312. The outlet 330 valve is then opened to allow for dispensing of the aerosol.

Figure 5a shows an aerosol metering valve herein and Figure 5b shows a detail 20 of this valve when the inlet valve is in the open position. The metering valve comprises a valve body 410 which defines a metering chamber 412 and a sampling chamber 414. The metering chamber has an inlet 420 permitting flow 25 of aerosol from the sampling chamber 414 and an outlet 430 permitting dispensing of aerosol from the metering chamber 412. The inlet 420 is provided with valve means comprising a valve seat 422 and a valve poppet in the form of a resilient ball 424. The ball 424 is biased towards the valve seat 422 by the action of spring 426. The outlet 430 is also provided with valve means 30 comprising a valve poppet in the form of a resilient ball 434 biased into contact with a valve seat 432 by action of spring 436. Shaped, flexible elastomer bags 440, 442 sit within and on both sides of access holes 416, 418 provided in the sampling chamber 414 and metering chamber 412 respectively. The elastomer bags 440, 442 contain fluid material. It may be seen that one portion of each of 35 the elastomer bags 440, 442 contacts the resilient balls 424, 434 of the inlet 420

and outlet 430 valves respectively. It may also be seen that another portion of each of the elastomer bags 440, 442 contacts an impacting arm 450 which is pivoted at pivot 454. The impacting arm 450 is itself connected to handle 456 which may itself be attached to a breath-actuable vane (not shown).

5

Actuation of the metering valve of Figures 5a and 5b is achievable by impacting the flexible, fluid-filled elastomer bags 440, 442 to physically dislodge the resilient balls 424,434 from their respective seats 422, 432. Impaction of the elastomer bags 440, 442 is in turn achievable by the impacting movement of the impacting arm 450. The bags 440, 442 are shaped such as to deform upon impact to allow for transfer of the energy of impaction through the fluid contents. The deformation of one of the bags 440 on being struck by the impacting arm 450 is shown in Figure 5b which also shows the dislodgement of the resilient ball 424 from its seat 422. In a typical operation the inlet 420 valve will first be opened to allow metered flow of aerosol into the metering chamber 412. The outlet 430 valve is then opened to allow for dispensing of the aerosol. It will be appreciated that the illustrated pivotal mounting 454 of the impacting arm 450 only allows for impaction of one of the elastomer bags 440,442, and hence opening of only one of the inlet 420 or outlet 430 valves, at a time.

20

Figure 6 shows an aerosol metering valve herein. The valve comprises a valve body 510 which defines a metering chamber 512 and a sampling chamber 514. The metering chamber has an inlet 520 permitting flow of aerosol from the sampling chamber 514 and an outlet 530 permitting dispensing of aerosol from the metering chamber 512. The inlet 520 is provided with valve means comprising a valve seat 522 and a valve poppet in the form of a resilient ball 524. The ball 524 is biased towards the valve seat 522 by the action of spring 526. The outlet 530 is also provided with valve means comprising a valve poppet in the form of a ball 534 biased into contact with a valve seat 532 by action of spring 536. The valve body 510 is within a housing 506 and the housing is provided with fixing screws 505, 507 for fixing the valve to an aerosol container 503 (shown in part only). Shaped pins 540, 542 sit within and on both sides of access holes 516, 518 provided in the sampling chamber 514 and metering chamber 512 respectively. It may be seen that the tail end of each of the shaped pins 540, 542 contacts the resilient balls 524, 534 of the inlet 520 and outlet 530

25

30

35

valves respectively. It may also be seen that the head of each of the pins 540, 542 contacts an elastomer diaphragm 546, 548 which in turn contacts double-headed transfer pins 546, 548. The elastomer diaphragms 546, 548 and the transfer pins 550, 552 are mounted in side compartments of the valve body. The outer heads of the transfer pins 546, 548 are impactable by an impacting arm 560 which is pivoted at pivot 564. The impacting arm 560 may itself be connected to a breath-actuable vane (not shown).

- Actuation of the metering valve of Figure 6 is achievable by movement of the shaped pins 540, 542 to physically dislodge the resilient balls 524, 534 from their respective seats 522, 532. Movement of the shaped pins 540, 542 is in turn achievable by impacting the elastomer diaphragms 546, 548 with their respective transfer pins 550, 552 following an impact by the impacting arm 560. In a typical operation the inlet 520 valve will first be opened to allow metered flow of aerosol into the metering chamber 512. The outlet 530 valve is then opened to allow for dispensing of the aerosol. It will be appreciated that the illustrated pivotal mounting 564 of the impacting arm 560 only allows for impactation of one of the transfer pins 550, 552, and hence opening of only one of the inlet 520 or outlet 530 valves, at a time.
- Figure 7 shows a simplified, schematic representation of a poppet valve actuation mechanism suitable for use in an aerosol metering valve herein. The metering valve might, for example be of a type similar to those shown in Figures 1 to 6 but including the poppet valve actuation mechanism now described. The portion of the valve body 610 which defines a metering chamber 612 is shown. The metering chamber has an outlet 630 permitting dispensing of aerosol from the metering chamber 612. The outlet 630 is provided with valve means comprising a valve poppet in the form of a resilient ball 634 biased into contact with a valve seat 632 by action of spring 636. An actuator rod 642 sits within and on both sides of an access hole 618 provided in the metering chamber 612. The tail end of the actuator rod 642 contacts the resilient ball 634 of the outlet 630 valve. The shaft of the actuator rod 642 is housed within torque tube 652 and a handle 656 is provided to the head of the actuator rod 642.

Actuation of the valve of Figure 7 is achievable by rotating the actuator rod 642 such that its tail end physically dislodges the resilient ball 634 from its seat 622. The actuator rod 642 is rotated by use of the handle 656 at its head. The handle 656 may be coupled to any suitable drive means including mechanical and electrical drive means (not shown).

Figures 8a to 8d show various forms of poppet valve suitable for use in accord with the invention. These employ valve poppets having different forms. These alternative valve poppets may be used in the metering valves of Figures 1 to 6 or the poppet valve actuation mechanism of Figure 7 instead of the ball valve poppets shown therein.

In more detail, Figures 8a to 8d show a valve body 710a-d supporting a valve seat 732a-d and a valve poppet 734a-d which sits on valve seat 732a-d. In Figure 8a the valve poppet 734a is in the form of a mushroom. In Figure 8b the valve poppet 734b is in the form of a cone. In Figure 8c the valve poppet 734c is in the form of a disc. In Figure 8d the valve poppet 734d is in the form of a plug.

Figure 9 shows an aerosol metering valve herein in the rest position. The valve comprises a valve body 810 which defines a metering chamber 812 and a sampling chamber 814. The metering chamber has an inlet 820 permitting flow of aerosol from the sampling chamber 814 and an outlet 830 permitting dispensing of aerosol from the metering chamber 812. The inlet 820 is provided with valve means comprising a valve seat 822 and a valve poppet in the form of a first shaped magnet 824 which has a flexible seal 823 provided thereto. The seal 823 is biased away from the valve seat 822 by the repulsive action of toroidal magnet 850. The outlet 830 is also provided with valve means comprising a valve poppet in the form of a second shaped magnet 834 having a flexible seal 833 biased into contact with a valve seat 832 by the attractive action of toroidal magnet 850. Both shaped magnets 824, 834 are chamfered to provide flow passageways therethrough.

Actuation of the metering valve of Figure 9 is achievable by movement of the toroidal magnet 850 downwards which removes the repulsive force from the first shaped magnet 824 which may therefore contact the valve seat 822 closing the

inlet 820. Simultaneously, the toroidal magnet 850 attracts the second shaped magnet 834 which moves off its seat 832 thereby opening the outlet 830. The toroidal magnet 850 may in turn be coupled to a mechanical trigger such as a lever mechanism (not shown).

5

Figure 10 shows an aerosol metering valve herein. The metering valve comprises a valve body 910 which defines a metering chamber 912 and a sampling chamber 914. The sampling chamber 914 is funnel-shaped to encourage ready flow of aerosol from the container to the metering chamber 912. The metering chamber 912 has an inlet 920 permitting flow of aerosol from the sampling chamber 914 and an outlet 930 permitting dispensing of aerosol from the metering chamber 912. The inlet 920 is provided with valve means comprising a valve seat 922 and a valve poppet in the form of a resilient ball 924. The ball 924 is biased towards the valve seat 922 by the action of spring 926. The outlet 930 is also provided with valve means comprising a valve poppet in the form of a resilient ball 934 biased into contact with a valve seat 932 by action of spring 936. The valve body 910 is provided with fixing screws 905, 907 for fixing the valve to an aerosol container 903 (shown in part only). Shaped pins 940, 942 sit within and on both sides of access holes 916, 918 provided in the sampling chamber 914 and metering chamber 912 respectively. It may be seen that the tail end of each of the shaped pins 940, 942 contacts the resilient balls 924, 934 of the inlet 920 and outlet 930 valves respectively. It may also be seen that each of the pins 940, 942 is biased to a rest position by spring 944, 946 away from the respective resilient ball 924, 934. The outer heads of the transfer pins 941, 943 are shaped for impact. A suitable impactor (not shown) might for example, comprise an impacting arm as shown in Figure 6 which may itself be connected to a breath-actuable vane.

Actuation of the metering valve of Figure 10 is achievable by impacting the heads 941, 943 of the shaped pins 940, 942 to physically dislodge the resilient balls 924, 934 from their respective seats 922, 932. The action of the springs 944, 946 will return each pin to the rest position on removal of the impacting force. In a typical operation the inlet 920 valve will first be opened to allow metered flow of aerosol into the metering chamber 912. The outlet 930 valve is then opened to allow for dispensing of the aerosol. The impactor may be

configured to allow for impaction of one of the shaped pins 940, 942, and hence opening of only one of the inlet 920 or outlet 930 valves, at a time.

- Figure 11 shows an aerosol metering valve herein. The metering valve
- 5 comprises a valve body 1010 which defines a metering chamber 1012 and a sampling chamber 1014. The metering chamber 1012 has an inlet 1020 permitting flow of aerosol from the sampling chamber 1014 and an outlet 1030 permitting dispensing of aerosol from the metering chamber 1012. The inlet 1020 is provided with valve means comprising a valve seat 1022 and a valve
- 10 poppet in the form of a cone 1024. The cone 1024 is biased towards the valve seat 1022 by the action of spring 1026 (rest position). The outlet 1030 is also provided with valve means comprising a valve poppet in the form of a cone 1034 biased into contact with a valve seat 1032 by action of spring 1036 (rest position). Shaped actuator pins 1040, 1042 sit within and on both sides of
- 15 access passages 1016, 1018 provided in the valve body 1010. It may be seen that the tail end of each of the actuator pins 1040, 1042 connects with the cone poppets 1024, 1034 of the inlet 1020 and outlet 1030 valves respectively. It may also be seen that the tail end each of the pins 1040, 1042 is provided with protective bellow seals 1046, 1048 which provide a seal between the cone
- 20 poppets 1024, 1034 and the actuator pins 1040, 1042. The outer heads of the transfer pins 1041, 1043 are shaped for impact. A suitable impactor (not shown) might for example, comprise an impacting arm as shown in Figure 6 which may itself be connected to a breath-actuable vane.
- 25 Actuation of the metering valve of Figure 11 is achievable by impacting the heads 1041, 1043 of the actuator pins 1040, 1042 to physically dislodge the cone poppets 1024, 1034 from their respective seats 1022, 1032. The action of the springs 1026, 1036 will return each pin 1040, 1042 to the rest position on removal of the impacting force. In a typical operation the inlet 1020 valve will first
- 30 be opened to allow metered flow of aerosol into the metering chamber 1012. The outlet 1030 valve is then opened to allow for dispensing of the aerosol. The impactor may be configured to allow for impaction of one of the actuator pins 1040, 1042, and hence opening of only one of the inlet 1020 or outlet 1030 valves, at a time.

Figure 12 shows an aerosol metering valve and aerosol container (in part) herein. The valve comprises a valve body 1110 which defines a metering chamber 1112 and a sampling chamber 1114. The sampling chamber 1114 has inlets 1116, 1117 permitting flow of aerosol from the aerosol container 1105. The metering chamber 1112 has an inlet 1120 permitting flow of aerosol from the sampling chamber 1114 and an outlet 1130 permitting dispensing of aerosol from the metering chamber 1112. The inlet 1120 is provided with valve means comprising a valve seat 1122 and a valve poppet in the form of a sliding piston 1124 with poppet head 1125. The poppet head 1125 of the sliding piston 1124 is biased towards the valve seat 1122 by the action of spring 1126. The outlet 1130 is also provided with valve means comprising a valve poppet in the form of a sliding piston 1134 with poppet head 1135 biased into contact with a valve seat 1132 by action of spring 1136. It may be seen that the bodies of sliding pistons 1124 and 1134, and their respective biasing springs 1126 and 1136, are respectively enclosed in hermetically sealed piston shafts 1128 and 1138. The ball-shaped 1125, 1135 poppet heads of the sliding pistons 1124, 1134 however, protrude from the piston shafts to contact the respective valve seats 1122, 1132. Shape memory alloy wires 1140, 1142 are fixed to the sliding pistons 1124, 1134 of the inlet 1120 and outlet 1130 valves respectively. The wires 1140, 1142 are also fixed to anchor points 1146, 1148 at the top of each respective piston shaft 1128, 1138. The wires 1140, 1142 are formed from a nickel-titanium alloy which contracts on heating, for example in response to electrical current flow. The wires 1140, 1142 are each connected to an electrical power source 1150, 1152.

Actuation of the metering valve of Figure 12 is achievable by contraction of the shape memory alloy wires 1140, 1142 to move the sliding pistons 1124, 1134 within their respective shafts 1128, 1138 and hence to move the poppet heads 1125, 1135 from their respective seats 1122, 1132. Contraction of the wires 1140, 1142 is in turn achievable by the flow of electrical current through the wires 1140, 1142. In a typical operation the inlet 1120 valve will first be opened to allow metered flow of aerosol into the metering chamber 1112. The outlet 1130 valve is then opened to allow for dispensing of the aerosol.

Figure 13 shows an aerosol metering valve herein which is a variation of the metering valve of Figure 9. The valve comprises a valve body 1210 which defines a metering chamber 1212 and a sampling chamber 1214. The valve body 1210 is provided with fixing holes 1205, 1207 for screw-fixing the valve to an aerosol container (not shown). The metering chamber has an inlet 1220 permitting flow of aerosol from the sampling chamber 1214 and an outlet 1230 permitting dispensing of aerosol from the metering chamber 1212. The inlet 1220 has a bore which is narrow for ease of aerosol flow, typically being approximately 2mm in diameter. The inlet 1220 is provided with valve means comprising a valve seat 1222 and a valve poppet in the form of a first shaped magnet 1224 which has a flexible ball head 1223 provided thereto. As shown, the magnet 1224 is biased away from the valve seat 1222 by the repulsive action of toroidal magnet 1250. When so biased away from the valve seat 1222, the magnet 1224 may move to position 1224a in which it abuts inclined surface 1209 at the mouth of the sampling chamber 1214 thereby permitting good aerosol flow to the inlet 1220 of the metering chamber 1212. The sampling chamber 1214 is also provided with slots 1215a, 1215b to further assist aerosol flow. The outlet 1230 has valve means comprising a valve poppet in the form of a second shaped magnet 1234 having a flexible ball head 1233 in contact with valve seat 1232. The metering chamber 1212 is provided with slots 1213a, 1213b to further assist aerosol flow. Both shaped magnets 1224, 1234 are chamfered to provide flow passageways therethrough.

Actuation of the metering valve of Figure 13 is achievable by movement of the toroidal magnet 1250 downwards which removes the repulsive force from the first shaped magnet 1224 which may therefore contact the valve seat 1222 closing the inlet 1220. Simultaneously, the toroidal magnet 1250 attracts the second shaped magnet 1234 which moves off its seat 1232 thereby opening the outlet 1230. The toroidal magnet 1250 may in turn be coupled to a mechanical trigger such as a lever mechanism (not shown).

Figure 14 shows an aerosol metering valve herein. The metering valve comprises a valve body 1310 which defines a metering chamber 1312 and a sampling chamber 1314. The valve body 1310 is provided with fixing screws 1305, 1307 for fixing the valve to an aerosol container (not shown).

The sampling chamber 1314 is funnel-shaped to encourage ready flow of aerosol from the container to the metering chamber 1312. The metering chamber 1312 has an inlet 1320 permitting flow of aerosol from the sampling chamber 1314 and an outlet 1330 permitting dispensing of aerosol from the 5 metering chamber 1312. The inlet 1320 is provided with valve means comprising a valve seat 1322 in the form of a rubber o-ring and a valve poppet in the form of a resilient ball 1324. The outlet 1330 is also provided with valve means comprising a valve poppet in the form of a resilient ball 1334 contacting valve seat 1332. Actuator rods 1340, 1350 are snugly received by cavities in the 10 resilient balls 1324, 1334 of the respective inlet and outlet valve poppets. The actuator rods 1340, 1350 also thread through resilient ball seals 1342, 1352 which sit within o-rings 1344, 1354 to form pivot seals. It may be appreciated that the ball poppets 1324, 1334 are movable by a pivoting (i.e. seesaw) movement of their respective actuator rods 1340, 1350 within the respective 15 pivot seals. The ends 1346, 1356 of the actuator rods 1340, 1350 are biased by the action of torsion springs 1348, 1358 which act on the rods 1340, 1350 such that the poppet seals 1324, 1334 are biased to the closed position. The springs 1348, 1358 are attached to arms 1360, 1362 which protrude from the upper part of the valve body 1310. Stops 1364, 1366 are provided to prevent excessive 20 movement of the actuator rods 1340, 1350 in the vertical (i.e. up/down) direction. The actuator rods 1340, 1350 may be connected to suitable breath-actuable vanes (not shown) to enable breath-actuation thereof.

Actuation of the metering valve of Figure 14 is achievable by pivoting the 25 actuator rods 1340, 1350 to dislodge the resilient balls 1324, 1334 from their respective seats 1322, 1332. The action of the springs 1348, 1358 will return each rod 1340, 1350 and associated ball poppet 1324, 1334 to the rest position on removal of the pivoting force. In a typical operation the inlet 1320 valve will first be opened to allow metered flow of aerosol into the metering chamber 1312. 30 The outlet 1330 valve is then opened to allow for dispensing of the aerosol. The valve operation will typically be configured to allow for pivoting of one of the actuator rods 1340, 1350 and hence opening of only one of the inlet 1320 or outlet 1330 valves, at a time.

- Figure 15 shows a schematic representation of an inhalation device herein. The device comprises a housing 1460 including a mouthpiece 1462 and shaped for receipt of an aerosol container 1470. The aerosol container 1470 has a metering valve 1472 which may be any metering valve described herein. Within the aerosol container 1470 is provided stirrer 1471 for assisting in the agitation of the aerosol contents thereof prior to dispensing. The metering valve 1472 has a valve stem 1474 including a valve nozzle 1476 for dispensing aerosol 1478 therefrom. The metering valve 1472 connects with valve driver system 1480 which may comprise any of the valve driver or trigger elements described herein.
- The valve driver system 1480 in turn communicates with breath sensor system 1490 which may comprise any breath sensing mechanism described herein. Dose counter 1492 is provided to count the number of actuations of the valve 1472 and may be connected to a display (not shown) to display doses dispensed or doses remaining in the container 1470.
- It may be appreciated that any of the parts of the metering valve which contact the medicament suspension may be coated with materials such as fluoropolymer materials which reduce the tendency of medicament to adhere thereto. Suitable fluoropolymers include polytetrafluoroethylene (PTFE) and fluoroethylene propylene (FEP). Any movable parts may also have coatings applied thereto which enhance their desired movement characteristics. Frictional coatings may therefore be applied to enhance frictional contact and lubricants used to reduce frictional contact as necessary.
- The aerosol container and valve of the invention is suitable for dispensing medicament, particularly for the treatment of respiratory disorders such as asthma and chronic obstructive pulmonary disease (COPD).
- Appropriate medicaments may thus be selected from, for example, analgesics, e.g., codeine, dihydromorphine, ergotamine, fentanyl or morphine; anginal preparations, e.g., diltiazem; antiallergics, e.g., cromoglycate, ketotifen or nedocromil; antiinfectives e.g., cephalosporins, penicillins, streptomycin, sulphonamides, tetracyclines and pentamidine; antihistamines, e.g., methapyrilene; anti-inflammatories, e.g., beclomethasone dipropionate, fluticasone propionate, flunisolide, budesonide, rofleponide, mometasone furoate

- or triamcinolone acetonide; antitussives, e.g., noscapine; bronchodilators, e.g., albuterol, salmeterol, ephedrine, adrenaline, fenoterol, formoterol, isoprenaline, metaproterenol, phenylephrine, phenylpropanolamine, pirbuterol, reproterol, rimiterol, terbutaline, isoetharine, tulobuterol, or (-)-4-amino-3,5-dichloro- α -[[[6-[2-(2-pyridinyl)ethoxy] hexyl]methyl] benzenemethanol; diuretics, e.g., amiloride; anticholinergics, e.g., ipratropium, tiotropium, atropine or oxitropium; hormones, e.g., cortisone, hydrocortisone or prednisolone; xanthines, e.g., aminophylline, choline theophyllinate, lysine theophyllinate or theophylline; therapeutic proteins and peptides, e.g., insulin or glucagon. It will be clear to a person skilled in the art that, where appropriate, the medicaments may be used in the form of salts, (e.g., as alkali metal or amine salts or as acid addition salts) or as esters (e.g., lower alkyl esters) or as solvates (e.g., hydrates) to optimise the activity and/or stability of the medicament.
- Preferred medicaments are selected from albuterol, salmeterol, fluticasone propionate and beclomethasone dipropionate and salts or solvates thereof, e.g., the sulphate of albuterol and the xinafoate of salmeterol.
- Medicaments can also be delivered in combinations. Preferred formulations containing combinations of active ingredients contain salbutamol (e.g., as the free base or the sulphate salt) or salmeterol (e.g., as the xinafoate salt) in combination with an antiinflammatory steroid such as a beclomethasone ester (e.g., the dipropionate) or a fluticasone ester (e.g., the propionate).
- It will be understood that the present disclosure is for the purpose of illustration only and the invention extends to modifications, variations and improvements thereto.
- The application of which this description and claims form part may be used as a basis for priority in respect of any subsequent application. The claims of such subsequent application may be directed to any feature or combination of features described therein. They may take the form of product, method or use claims and may include, by way of example and without limitation, one or more of the following claims:

PG3671 – PCT filing

25

Claims

5

1. Metering valve for use as the metering valve of an aerosol container for dispensing medicament comprising

a valve body defining a metering chamber;

10

said metering chamber having an inlet and an outlet, said inlet permitting flow of aerosol from said container to the metering chamber and said outlet permitting dispensing of aerosol from the metering chamber;

15

the inlet having an inlet valve reversibly actuatable from an open to a closed position; and

the outlet having an outlet valve reversibly actuatable from a dispensing to a non-dispensing position, said outlet valve comprising an outlet valve seat and an

20

outlet valve poppet in biasable contact therewith, the outlet valve being closed when the metering valve is at rest; and

an outlet valve mover for moving the outlet valve poppet out of contact with the valve seat, thereby enabling dispensing of the aerosol without requiring

25

movement of any other dispensing member relative to the valve body.

2. Metering valve according to claim 1, wherein said inlet valve comprises an inlet valve seat and an inlet valve poppet in biasable contact therewith.

30

3. Metering valve according to either of claims 1 or 2, wherein the inlet valve is closed when the metering valve is at rest.

4. Metering valve according to any of claims 1 to 3, wherein the inlet valve and the outlet valve are independently operable.

35

PG3671 – PCT filing

26

5. Metering valve according to any of claims 1 to 4, wherein any valve poppet comprises an incompressible material and any valve seat comprises a compressible material.
10. 6. Metering valve according to any of claims 1 to 4, wherein any valve poppet comprises a compressible material and any valve seat comprises an incompressible material.
15. 7. Metering valve according to any of claims 2 to 6; additionally comprising an inlet valve mover for moving the inlet valve poppet out of contact with the inlet valve seat.
20. 8. Metering valve according to any of claims 1 to 7, wherein said outlet valve mover and said inlet valve mover are independently operable.
9. 9. Metering valve according to either of claims 7 or 8, wherein either or both of said inlet valve mover or said outlet valve mover is mechanically actuatable.
10. 10. Metering valve according to either of claims 7 or 8, wherein either or both of the inlet valve mover or the outlet valve mover is electrically actuatable.
25. 11. Metering valve according to claim 10, wherein either or both of the inlet valve mover or the outlet valve mover comprises a multi-component strip or wire which is deformable in response to electrical current flow.
30. 12. Metering valve according to claim 11, wherein said multi-component strip or wire comprises multiple layers of different metals.
13. 13. Metering valve according to claim 12, wherein the multi-component strip comprises a bimetallic strip.
35. 14. Metering valve according to either of claims 11 or 12, wherein the multi-

PG3671 – PCT filing

26a

component strip comprises at least one piezoelectric or piezoresistive material.

5

15. Metering valve according to claim 11, wherein said multi-component wire comprises a nickel-titanium alloy.

10

16. Metering valve according to either of claims 7 or 8, wherein either or both of the inlet valve mover or the outlet valve mover is magnetically actuatable.

17. Metering valve according to claim 16, wherein either or both of the inlet valve mover or the outlet valve mover comprises magnetic material or material which is magnetically inductive.
- 5 18. Metering valve according to either of claims 7 or 8, wherein either or both of the inlet valve mover or the outlet valve mover is pneumatically actuatable.
- 10 19. Metering valve according to either of claims 7 or 8, wherein either or both of the inlet valve mover or the outlet valve mover is hydraulically actuatable.
- 10 20. Metering valve according to claim 18, wherein either or both of the inlet valve mover or the outlet valve mover comprises a fluid-filled bag or tube capable of transferring hydraulic force.
- 15 21. Metering valve according to any of claims 1 to 20, wherein the outlet valve poppet has a form selected from the group consisting of a ball, a mushroom, a cone, a disc and a plug.
- 20 22. Metering valve according to any of claims 2 to 21, wherein the inlet valve poppet has a form selected from the group consisting of a ball, a mushroom, a cone, a disc and a plug.
- 25 23. Metering valve according to any of claims 1 to 22, wherein said valve body additionally defines a sampling chamber and the inlet permits flow from the sampling chamber to the metering chamber.
- 25 24. Metering chamber according to any of claims 1 to 23, wherein the metering chamber has a fixed volume.
- 30 25. Metering valve according to any of claims 1 to 23, wherein the metering chamber has a variable metering volume.
- 30 26. Aerosol container comprising a metering valve according to any of claims 1 to 25.

27. Aerosol container according to claim 26, wherein the valve body of the metering valve is not movable relative to the container.
28. Aerosol container according to either of claims 26 or 27 comprising a suspension of a medicament in a propellant.
29. Aerosol container according to claim 28, wherein, said propellant comprises liquefied HFA134a, HFA-227 or carbon dioxide.
30. Aerosol container according to either of claims 28 or 29, wherein the medicament is selected from the group consisting of albuterol, salmeterol, fluticasone propionate, beclomethasone dipropionate, salts or solvates thereof and any mixtures thereof.
31. Aerosol container according to either of claims 28 or 29 comprising a compressed gas, preferably compressed air.
32. Inhalation device for dispensing medicament to a patient comprising a housing; an aerosol container, locatable within said housing, said aerosol container comprising a metering valve according to any of claims 1 to 25; and an outlet valve trigger for triggering the movement of the outlet valve poppet out of contact with the outlet valve seat.
33. Inhalation device according to claim 32, wherein the aerosol container comprises a metering valve according to any of claims 2 to 25, additionally comprising an inlet valve trigger for triggering the movement of the inlet valve poppet out of contact with the inlet valve seat.
34. Inhalation device according to either of claims 32 or 33, wherein either or both of said outlet valve trigger or said inlet valve trigger is triggerable in response to the breath of a patient.

35. Inhalation device according to claim 34, wherein either or both of the outlet valve trigger or the inlet valve trigger is triggerable in response to the inward breath of a patient.
- 5 36. Inhalation device according to claim 34, wherein either or both of the outlet valve trigger or the inlet valve trigger is triggerable at a trigger point which is coupled to the end of the exhalation part of a patient's breath cycle.
- 10 37. Inhalation device according to any of claims 34 to 36, wherein either or both of the outlet valve trigger or the inlet valve trigger communicates with a sensor which senses the breath of a patient.
- 15 38. Inhalation device according to claim 37, wherein said sensor comprises a breath-movable element which is movable in response to the breath of a patient.
39. Inhalation device according to claim 38, wherein said breath-movable element is selected from the group consisting of a vane, a sail, a piston and an impeller.
- 20 40. Inhalation device according to claim 37, wherein said sensor comprises a pressure sensor for sensing the pressure profile associated with the breath of a patient.
- 25 41. Inhalation device according to claim 37, wherein said sensor comprises an airflow sensor for sensing the airflow profile associated with the breath of a patient.
- 30 42. Inhalation device according to claim 37, wherein said sensor comprises a temperature sensor for sensing the temperature profile associated with the breath of a patient.
- 35 43. Inhalation device according to claim 37, wherein said sensor comprises a moisture sensor for sensing the moisture profile associated with the breath of a patient.

44. Inhalation device according to claim 37, wherein said sensor comprises a gas sensor for sensing the oxygen or carbon dioxide profile associated with the breath of a patient.
- 5 45. Inhalation device according to claim 37, wherein said sensor comprises a piezoelectric or piezoresistive element.
- 10 46. Inhalation device according to any of claims 32 to 45, wherein the outlet valve trigger and the inlet valve trigger are independently triggerable.
- 15 47. Inhalation device according to any of claims 32 to 45, wherein the outlet valve trigger and the inlet valve trigger are triggerable in a coupled fashion.
- 20 48. Inhalation device according to any of claims 32 to 47, wherein either or both of the outlet valve trigger or the inlet valve trigger is a mechanical trigger.
49. Inhalation device according to claim 48, wherein said mechanical trigger comprises a lever mechanism.
50. Inhalation device according to claim 48, wherein said mechanical trigger comprises a torque transfer mechanism.
- 25 51. Inhalation device according to any of claims 32 to 47, wherein either or both of the outlet valve trigger or the inlet valve trigger comprises a multi-component strip which is deformable in response to electrical current flow.
- 30 52. Inhalation device according to claim 51, wherein said multi-component strip comprises multiple layers of different metals.
53. Inhalation device according to claim 52, wherein said multi-component strip comprises a bimetallic strip.

54. Inhalation device according to either of claims 51 or 52, wherein said multi-component strip comprises at least one piezoelectric or piezoresistive material.
- 5 55. Inhalation device according to any of claims 32 to 47, wherein either or both of the outlet valve trigger or the inlet valve trigger is a magnetic trigger.
- 10 56. Inhalation device according to claim 55, wherein the outlet valve trigger interacts magnetically with the outlet valve poppet and/or the inlet valve trigger interacts magnetically with the inlet valve poppet.
- 15 57. Inhalation device according to claim 55, wherein the outlet valve trigger interacts magnetically with a outlet shuttle contacting the outlet valve poppet and/ or the inlet valve trigger interacts magnetically with a inlet shuttle contacting the inlet valve poppet.
58. Inhalation device according to claim 57, wherein the outlet shuttle and/or inlet shuttle comprises magnetic material.
- 20 59. Inhalation device according to either of claims 57 or 58, wherein the outlet shuttle comprises material which is magnetically inductive and the outlet valve trigger comprises an inductive element capable of inducing magnetism therein and/or the inlet shuttle comprises material which is magnetically inductive and the inlet valve trigger comprises an inductive element capable of inducing magnetism therein.
- 25 60. Inhalation device according to any of claims 32 to 47, wherein either or both of the outlet valve trigger or the inlet valve trigger is a pneumatic trigger.
- 30 61. Inhalation device according to any of claims 32 to 47, wherein either or both of the outlet valve trigger or the inlet valve trigger is a hydraulic trigger.
62. Inhalation device according to claim 61, wherein the hydraulic trigger comprises a fluid-filled bag or tube capable of transferring hydraulic force.

32

63. Use of an inhalation device according to any of claims 32 to 62 for the delivery of inhalable medicament to a patient.

5

10

15

1 / 14




FIG.1.

2 / 14




FIG. 2.

3 / 14




FIG. 3.

4 / 14




FIG. 4.

5 / 14




FIG. 5a.




FIG. 5b.

6 / 14




FIG. 6.

7 / 14




FIG. 7.




FIG. 8a.




FIG. 8b.




FIG. 8c.




FIG. 8d.

8 / 14




FIG. 9.

9 / 14





FIG. 10.

10 / 14



11/14




FIG.12.

12 / 14




FIG. 13.

13 / 14




FIG. 14.

14 / 14




FIG. 15.

DECLARATION FOR "371" APPLICATION

**COMBINED DECLARATION FOR UTILITY OR DESIGN PATENT
APPLICATION WITH POWER OF ATTORNEY**

- () Declaration submitted with initial filing or
() Declaration submitted after initial filing (surcharge required 37CFR1.16(e))

ATTORNEY'S DOCKET PG3671USW
First Names Inventor Anthony Patrick JONES
<u>Complete if known:</u> App No.:
Filing Date
Group Art Unit:

As below named inventor. I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METERING VALVE

the specification of which (check only one item below):

[] is attached hereto.

OR

[x] was filed on **23 February 2000** as United States application Serial No. _____ or PCT International

Application Number **PCT/EP00/01446** filed and was amended on (MM/DD/YYYY) _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35, U.S.C. §119 (a)-(d) or §365(b) of any foreign applications(s) for patent or inventor's certificate or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or of any PCT international application having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. 119:

Prior Foreign Application Number (s)	Country	Foreign Filing Date (MM/DD/YYYY)	PRIORITY CLAIMED
1. 9905568.3	GB	March 12, 1999	X
2. 9918388.1	GB	August 5, 1999	X
3.			
4.			
5.			

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below:

Application No.	Filing Date (MM/DD/YYYY)
1.	
2.	
3.	
4.	

DECLARATION FOR "371" APPLICATION

**COMBINED DECLARATION FOR UTILITY or DESIGN
PATENT APPLICATION WITH POWER OF ATTORNEY** ContinuedATTORNEY'S DOCKET NUMBER
PG3671USW

I hereby claim the benefit under 35, U S C §120 of any United States application or §365(c) of any PCT international application designating the United States of America that is listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U S C §112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 C F R §1.56 which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application.

PRIOR U.S. PARENT APPLICATION or PCT PARENT APPLICATION

		STATUS (Check one)		
U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	PATENTED	PENDING	ABANDONED

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the U.S. Patent and Trademark Office connected therewith (List name and registration number)

David J. Levy	Reg No. 27,655	James P. Riek	Reg No. 39,009	Bonnie L. Deppenbrock Reg No 28,209
Charles E. Dadswell	Reg No 35,851	Virginia C. Bennett	Reg. No. 37,092	John L. Lemanowicz Reg No 37,380
Karen L. Prus	Reg. No. 39,337	Frank P. Grassler	Reg. No. 31,164	Amy H. Fix Reg. No. 42,616
Robert H. Brink	Reg No 36,094	Christopher P. Rogers	Reg No 36,334	
Elizabeth Selby	Reg No 38,298	Lorie Ann Morgan	Reg. No. 38,181	

Send Correspondence to:

David J. Levy, Patent Counsel
Corporate Intellectual Property Department
GlaxoSmithKline
Five Moore Drive, PO Box 13398
Research Triangle Park, NC 27709



23347

PATENT TRADEMARK OFFICE

Direct Telephone Calls to:

Christopher P. Rogers
919-483-1240

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

2	FULL NAME OF INVENTOR	FAMILY NAME JONES	FIRST GIVEN NAME Anthony	SECOND GIVEN NAME/INITIAL Patrick
0	INVENTOR'S SIGNATURE	Signature X <i>Patricia Jones</i>		
0	RESIDENCE & CITIZENSHIP	CITY Ware	STATE OR FOREIGN COUNTRY GB GBX	COUNTRY OF CITIZENSHIP GB
1	POST OFFICE ADDRESS	POST OFFICE ADDRESS GlaxoSmithKline Five Moore Drive, PO Box 13398	CITY Durham	STATE & ZIP CODE/COUNTRY North Carolina 27709, US
2	FULL NAME OF INVENTOR	FAMILY NAME ANDERSON	FIRST GIVEN NAME Gregor	SECOND GIVEN NAME/INITIAL John, McLennan
0	INVENTOR'S SIGNATURE	Signature X <i>Gregor Anderson</i>		
0	RESIDENCE & CITIZENSHIP	CITY Ware	STATE OR FOREIGN COUNTRY GB GBX	COUNTRY OF CITIZENSHIP GB
2	POST OFFICE ADDRESS	POST OFFICE ADDRESS GlaxoSmithKline Five Moore Drive, POBox 13398	CITY Durham	STATE & ZIP CODE/COUNTRY North Carolina 27709, US
2	FULL NAME OF INVENTOR	FAMILY NAME RAND	FIRST GIVEN NAME Paul	SECOND GIVEN NAME/INITIAL Kenneth
0	INVENTOR'S SIGNATURE	Signature X <i>Paul Kenneth Rand</i>		
0	RESIDENCE & CITIZENSHIP	CITY Ware	STATE OR FOREIGN COUNTRY GB GBX	COUNTRY OF CITIZENSHIP GB
3	POST OFFICE ADDRESS	POST OFFICE ADDRESS GlaxoSmithKline Five Moore Drive, POBox 13398	CITY Durham	STATE & ZIP CODE/COUNTRY North Carolina 27709, US